



INTERNATIONAL JOURNAL OF MULTIDISCIPLINARY RESEARCH

IN SCIENCE, ENGINEERING, TECHNOLOGY AND MANAGEMENT

Volume 10, Issue 4, April 2023



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 7.580



+91 99405 72462



+9163819 07438



ijmrsetm@gmail.com



www.ijmrsetm.com

Hybrid Energy Generation for Multi Vehicles Charging Station Model

Saiyyad Hibjul Raheman, Abdul Muiz Sheikh, Md Shoaib Khan, Sahil Sheikh, Tushar Tatte, Vishal Kumar
Suryawanshi

Students, Department of Electrical Engineering, Anjuman College of Engineering and Technology, Nagpur, India
Dr.Saiyyad Naimuddin, Project Guide, Department of Electrical Engineering, Anjuman College of Engineering and
Technology, Nagpur, India

Prof. Najma Siddiqui, Project Co-Guide, Department of Electrical Engineering, Anjuman College of Engineering and
Technology, Nagpur, India

ABSTRACT: The ultimate promise of electric vehicles is a cleaner environment. That cannot be achieved if the strain on the power grid requires additional investment in nonrenewable resources to deliver the energy. That's why renewable energy for EV charging is so critical. Using renewable energy to power the EV charging infrastructure eliminates the strain on the grid and the environment simultaneously, especially when paired with smart EV charging. The combination of solar panel systems, wind energy systems (both), and electric vehicles A charging station brings several benefits and provides a cost-effective way to produce and make use of solar energy, wind energy, or both. Recently, there has been significant research focused on smart cities and how to use resources efficiently. Parking space, in particular, is scarce in most metropolitan areas, and intelligent systems are required to coordinate parking. This paper presents a wireless charging system for EVs and a wireless sensor node that determines if parking spots are vacant or not. It was found that the system is highly efficient and has high accuracy, even at long ranges.

KEYWORDS: solar panel, Arduino uno, Relay Module, IR (Infrared Sensor), LCD Screen, RFID Sensor, Servo Motor, Battery, Tesla Coil, Charge controller.

I.INTRODUCTION

More than half of the world's population lives in urban areas, so the cities have reached full occupancy. As a result, the number of vehicles in the cities has also increased. Due to this, most people spend their valuable time searching for parking spaces to park their vehicles. It is a hectic job to find parking spaces to park their vehicles. The work proposed in this paper is an attempt to solve the problem mentioned above. A smart parking system is installed where you can charge your vehicles wirelessly in the parking station. There are smart gates. It's connected with an RFID sensor. Just scan the card, the gate will open, and you can pass through the card.

Wind and solar energy are nonconventional sources of energy and are available in abundance. Electricity can be generated with the help of a vertical-axis wind turbine. This project aims to utilize this wind energy in the most effective manner to get the maximum electric output, and therefore we selected a highway as our installation site, where we can take advantage of the moving vehicles on both sides of the road. (For 12 volts, we need to rotate at 7 m/s, or 25 kmph.). Solar and wind energy are stored in the batteries, and this energy is used to charge electric vehicles. The mode of charging is wireless. Wireless charging of electric vehicles (EVs) has been in development for several years in preparation for the growth in adoption of these vehicles. Wireless charging systems today offer an efficient, flexible means of charging EVs from multiple classes and at a range of power levels from a common ground source. Standardization activities are well underway to ensure compatibility between systems across vehicle makers and locations. This paper provides a snapshot of wireless charging technology as applied to EVs.


II.OBJECTIVE

The objective of this work is to design, analyse, and implement a "Hybrid Energy Generation for Multi-Vehicle Charging Station Model". The RFID parking system provides contactless access to the parking lot. This project's objective is to utilise this wind energy in the most effective manner to get the maximum electric output, and therefore we selected a highway as our installation site where we can take advantage of the moving vehicles on both sides of the road. Generate more energy than separate solar and wind power systems can provide. Hybrid systems can provide owners with improved supply reliability and security, especially if they are the only power source in an off-grid

environment. The main goal is to transmit power using resonance coupling and to build the charging systems. The systems deal with an AC source, transmission coil, reception coil, converter, and electric load, which are batteries.

III.METHODOLOGY

3.1 SENSOR BASED GATE



In smart gates, there are three main parts.

- 1) Arduino: We are using Arduino to operate different operations. In smart gates, the Arduino is connected to an RFID sensor. It is also connected to a servo motor.
- 2) RFID sensor: In RFID, a sensor is used to pay money and open the gate with the help of a servo motor. The RFID sensor detects whether the RFID card is authorized or not. If it is authorized, it will check the balance on your card and open the gate.
- 3) Servo motor: Following the RFID sensor, a servo motor is connected to the Arduino. After checking your information about the card, the Arduino gives the signal to the servo motor, which opens the gate.

3.2 HIGHWAY WIND TURBINE



3.2.1 MOVING VEHICLES

The vehicle moving on the highway has sufficient potential that can be used for generating the DC power by use of vertical axis wind turbine. The vertical axis wind turbine is placed on the highway to generate the power during normal wind flow as well as through the air force due to movement of vehicles on highways. Fins are designed in a similar manner as that of savonius rotor with a slight modification in the shape of upper and lower parts that are sinusoidally designed to increase the air force. The blades are design so as to optimize wind force. It can provide electricity to the streetlights at night hours and can supply dc energy to E-vehicle charging station.

3.2.2 NATURAL WIND

When a high amount of wind is blowing, the wind turbines also generate energy from the natural wind.

3.3 SOLAR BASED CHARGING




Solar chargers work by taking the energy absorbed through solar panels and using it to charge solar batteries. Multiple solar cells make up the solar panels and work to absorb sunlight and convert it into electricity. The solar batteries then store the energy produced by your solar panels for later use in wireless charging.


3.4 WIRELESS CHARGING STATION.

In wireless charging, the car is parked in a parking slot, and an IR sensor detects it, sending an input to the Arduino, which sends an output to the relay, which is connected to the battery and the transmitter coil. The transmitter coil creates a primary EM field extending in all directions. This causes eddy currents to flow in conductive objects. The eddy currents create a secondary field.


IV.BLOCK DIAGRAM



5.1 For RFID



5.2 for the IR sensor, relay, servo motor, and lcd display



We successfully built the smart parking station.

IJMRSETM©2023



REFERENCES

1. Vertical axis wind turbine for highways application [vol2(10,2016)], issn 2454- 1362 imperial journal of interdisciplinary reaserch (UIR) prof.arunkulkarnipune,india
2. M.K. Sharma "The study of wind energy potential from highway". In International Journal of Engineering Research and Technology, 2012.
3. "J Berrocal, Brian Dolan, M Tangredi" "Design of Vertical Axis Wind Turbine to Power Led Street Lights".
4. M.C.Claessens" "testing and design of aerofoils for Application in Small Scale Vertical Axis Wind Turbines
5. Guoying Feng, Zhinhang Liu, Bao Daorina, Zheng Gong"." Experimental Research on Vertically Wind Turbine", 2009 [9] www.Wikipedia.com
6. Peter J. Schubel and Richard J. Crossley", "Wind Turbine Blade Design" 2012
7. Al Tarabshch, I. Etier, H. Fath, A. Ghazal, Y. Morci, M. Asad, A. El Haj. "Performance of Photovoltaic Cells in Photovoltaic Thermal (PVT) Modules". IET Renewable Smart solar power plant:- This full-text paper was peer-reviewed and accepted to be presented at the IEEE ICCSP 2015 conference. Sam Jose and Dr. Raieshwari L Itagi
8. Wind Energy Systems:- Wind Energy Systems By Frede Blaabjerg, Fellow IEEE, and Ke Ma, Member IEEE.
9. Adilet Sultanbek, Auyez Khasenov, Yerassyl Kanapyanov, Madina Kenzhagaliyeva, and Mehdi Bagheri
10. "Intelligent Wireless Charging Station for Electric Vehicles" Electrical and Computer Engineering Department, School of Engineering in 2017 International Siberian Conference on Control and Communications (SIBCON).
11. Amol Pomaj, Suraj Boinwad, Shrikant Wankhede, Pushpendra Singh, Bhagyashree Dhakulkar
"Smart Parking Management System" on International Journal of Computer Sciences and Engineering.
12. S. Li, C.C. Mi, "Wireless power transfer for electric vehicle applications". IEEE Trans. Emerg. Sel. Topics Power Electron. 3, 4–17 (2015)
13. K.N. Mude, "Wireless power transfer for electric vehicle". PhD thesis, University of Padova, Italy (2015). Accessed 14 November 2020
14. J. Soler, The role of electromagnetic simulation in wireless charging systems, in Japan Altair Technology Conference (2017)
15. R.M. Duarte, G.K. Felic, Analysis of the coupling coefficient in inductive energy transfer systems. Active and Passive Electron. Compon. (2014). <https://doi.org/10.1155/2014/951624>
16. E. J. Jaselskis, T. El-Misalami (2003), "Implementing Radio Frequency Identification in the Construction Process" Journal of Construction Engineering and Management, ASCE, 129(6)
17. Wu, M.; Li, Z.; Fan, J. Selection of new energy vehicles using hybrid approach: A case study of China. IFS 2021, 40, 11967–11980.
18. Almezizia, A.A.; Al-Masri, H.M.K.; Ehsani, M. Feasibility Study of Sustainable Energy Sources in a Fossil Fuel Rich Country. IEEE Trans. Ind. Appl. 2019, 55, 4433–4440
19. Zhang, J.; Zhang, Y.; Li, T.; Jiang, L.; Li, K.; Yin, H.; Ma, C.L. A Hierarchical Distributed Energy Management for Multiple PV-Based EV Charging Stations. In Proceedings of the IECON 2018-44th Annual Conference of the IEEE Industrial Electronics Society, Washington, DC, USA, 21–23 October 2018; pp. 1603–1608
20. R.M. Duarte, G.K. Felic, Analysis of the coupling coefficient in inductive energy transfer systems. Active and Passive Electron. Compon. (2014). <https://doi.org/10.1155/2014/951624>
21. Solar PV-Based Electric Vehicle Charging Station for Security Bikes: A Techno-Economic and Environmental Analysis Aqib Shafiq, Sheeraz Iqbal, Salman Habib, Atiq ur Rehman, Anis ur Rehman, Ali Selim, Emad M. Ahmed, and Salah Kamel.
22. A gate sensor for construction logistics June 2008 DOI: [10.3846/isarc.20080626.100](https://doi.org/10.3846/isarc.20080626.100) Conference: The 25th International Symposium on Automation and Robotics in Construction.



INTERNATIONAL JOURNAL OF MULTIDISCIPLINARY RESEARCH

IN SCIENCE, ENGINEERING, TECHNOLOGY AND MANAGEMENT



+91 99405 72462



+91 63819 07438



ijmrsetm@gmail.com

www.ijmrsetm.com